

CLEANER/REMOVER

Ardrox® 9PR50

Non-chlorinated solvent for removing oil, grease and similar soils from metal surfaces.

PRIMARY APPLICATION

Ardrox® 9PR50 is a Class 2, Method C, AMS 2644 approved cleaner/remover. It is a quick drying, non-halogenated (non-chlorinated) solvent for removing oil, grease and similar soils from metal surfaces. It provides a high level of cleaning efficiency with operational safety. It is completely corrosion safe for use on both ferrous and non-ferrous alloys. **Ardrox® 9PR50** is an excellent penetrant remover.

TYPICAL PROPERTIES

Physical form.....	Clear, colorless liquid
Bulk density.....	6.25 lb/gal
Specific gravity.....	0.74
Flash point.....	52° F (11° C), PMCC
Boiling point.....	244° F
Vapor pressure.....	26 mm Hg @ 100° F (38° C)
VOC.....	740 g/l

APPROVALS

AMS 2644
ASTM E165
NAVSEA 250-1500-1
ASME Pressure Vessel & Boiler Code

Chemetall Oakite manufacturing facilities are QS-9000 and ISO 9001 certified.

METHOD OF USE

Use as received. Cleaning may be by hand wipe, brush, spray or dip. Dwell time will vary slightly depending upon severity of soil being removed. Penetrant removal is done by wiping off excess penetrant with a dry cloth, then dampen a cloth of lint-free tissue with **Ardrox® 9PR50** and wipe off remaining penetrant.

Do not flood test surface with cleaner/remover because sensitivity will be impaired.

NOTES ON USE

Use in a well-ventilated area; avoid concentrating vapors. Keep away from heat, sparks, or open flames. Vapors are flammable.

SAFETY AND HANDLING

Prior to handling and use of any of the materials referenced in this document, the Material Safety Data Sheets should be read and understood by all personnel in contact with these materials.

KEEP OUT OF REACH OF CHILDREN

STORAGE

Dry indoor storage is recommended, away from any incompatible materials referenced in Material Safety Data Sheets. All containers should be tightly closed when not in use.

DISPOSAL

Any disposal of the materials referenced in this document should be in accordance with all applicable federal, state, and local regulations.

Process solutions can contain components other than those present in the materials as supplied. Analysis of process solutions may be required prior to disposal.

Oakite Products, Inc. ("Oakite") warrants that the product or products described herein will conform with its published specifications. The products supplied by Oakite and information related to them are intended for use by buyers having necessary industrial skill and knowledge. Buyers should undertake sufficient verification and testing to determine the suitability of the Oakite materials for their own particular purpose. Since buyer's conditions of use of products are beyond Oakite's control, Oakite does not warrant any recommendations and information for the use of such products. OAKITE DISCLAIMS ALL OTHER WARRANTIES INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR ANY PARTICULAR PURPOSE IN CONNECTION WITH THE USE OF ITS PRODUCTS.

Chemetall
Oakite



Oakite Products, Inc. P.O. Box 602, 50 Valley Road, Berkeley Heights, NJ 07922 • **Oakite Canada Limited** 115 East Drive, Bramalea, Ontario L6T1B7
Tel. (800) 526-4473 (908) 464-6900 FAX (908) 464-4658 Web site: www.oakite.com E-Mail: oakite.products@chemetall.com
Distributors and Licensees Worldwide